

Free-standing Luminaire

ATARO HYBRID - DUS 424-96/D 121572000-00522292



fitted with

4 x regular fluorescent lamp T16 24W/840 G5
light colour neutral white, 4000 K, Color Rendering Index (CRI)=80

Energy efficiency category A

96 x Light-emitting diode

light colour neutral white, 3700-4300 K, Color Rendering Index (CRI)=80

adjustable electronic ballast; digital DALI

Energy efficiency index (EEL): A1 BAT

220-240V; 50/60Hz

approx. 146 W

direct/indirect

approx. 57 lm/W

structured screen

continuously dimmable

multi-function switch

work equipment

connected load

power consumption

light distribution

Light yield

glare-free

technology

usage

luminaire body

material

surface

colour

lamp cover

tubular section

material

surface

Form

colour of tubular section

luminaire base

Form

weight (net)

mains lead

fastening

special features

aluminium

painted

silver metallic

not permitted, without

steel tube

painted

tubular section upright

silver metallic

rectangular flat

approx. 23.0 kg

approx. 3.0 m; mains plug

CEE 7/VII

floor standing base

asymmetric radiation, luminaire head can be turned in an angle of $\pm 90^\circ$, separated; direct and indirect light individually adjustable



CEE 7/VII

distribution of luminous intensity

